



GG1500/GG8000 SERIES

Gasoline Generator

EPA/CE APPROVED

TECHNICAL DATA

| Model | GG1500 | GG2500 | GG3500 | GG4500 | GG 5500 | GG6500 | GG 8000 | | | | | | | |
|------------------------|---|-------------|-------------|---------|----------|---------|-----------------|---------|-------------|------|------|------|------|------|
| Type | Revolving Magnetic Field, single phase | | | | | | | | | | | | | |
| AC Frequency(Hz) | 60 | 50 | 60 | 50 | 60 | 50 | 60 | 50 | 60 | 50 | 60 | 50 | 60 | 50 |
| AC Output volatge(V) | 110;120;110/220;120/240,220;230;115/230 | | | | | | | | | | | | | |
| Cont.AC Output(VA) | 1000 | 900 | 2200 | 2000 | 2800 | 2500 | 3300 | 3000 | 4500 | 4000 | 5500 | 5000 | 6500 | 6000 |
| Max.AC Output(VA) | 1500 | 1000 | 2500 | 2200 | 3500 | 2800 | 4500 | 3300 | 5500 | 4500 | 6500 | 5500 | 7000 | 6500 |
| DC Output(V/A) | 12/8.3 | | | | | | | | | | | | | |
| Engine Model | 154F | 168F | 170F | 177F(E) | 188F(E) | 188F(E) | 188F(E) | 190F(E) | | | | | | |
| Type | Single cylinder, air-cooled, 4-stroke OHV | | | | | | | | | | | | | |
| Starting System | Recoil | | | | | | Recoil/Electric | | | | | | | |
| Fuel Tank Capacity(L) | 6 | 15 | 25 | | | | | | | | | | | |
| Packing Dimensions(mm) | 450x365x355 | 610x470x465 | 695x520x570 | | | | | | 710x550x570 | | | | | |
| Net Weight(kgs/lbs) | 28/61.7 | 45/99.2 | 47/103.6 | 68/150 | 80/176.4 | 83/183 | 83/183 | | | | | | | |
| Per 20' GP CNT | 432 | 168 | 128 | 128 | | | | | | | | | | |
| Per 40' GP CNT | 912 | 336 | 256 | 256 | | | | | | | | | | |

Option: 1. Night lamp 2. Wheel kits 3. Ampere meter